



Dear LEWISBins+ Customer;

Thank you for your interest in our products. You requested a Material Safety Data Sheet (MSDS) for the products we supply your facility.

Our products fall under an MSDS exemption since they are considered an "article" per the Federal Occupational Safety and Health Administration. (An excerpt of the OSHA Rule (29 C.F.R. Section 1910.1200) is printed below.)

1910.1200(b)(6)(v)(c) Hazard communication.

"Article" means a manufactured item other than a fluid or particle: (i) which is formed to a specific shape or design during manufacture; (ii) which has end use function(s) dependent in whole or in part upon its shape or design during end use; and (iii) which under normal conditions of use does not release more than very small quantities, e.g., minute or trace amounts of a hazardous chemical (as determined under paragraph (d) of this section), and does not pose a physical hazard or health risk to employees.

To assist you in your request for material information I have included an MSDS that is typical of the base materials in the products we manufacture for your company. We cannot certify that this is from the specific manufacturer who supplied the resin at the time we produced your product but it will help you in your analysis of the material. If you should have additional questions or require additional information, please feel free to call your sales person or contact me directly at 262-560-5297. Thank you for allowing us the opportunity to be of service.

Regards,

Robert Nussbaum
Director New Product Development

Corporate Headquarters

1055 Corporate Center Drive

Oconomowoc, WI 53066 USA

Phone: 262.560.5700

Toll-Free Phone: 877-975-3947

Toll-Free Fax: 877-985-3947

e-mail: info@lewisbins.com

www.lewisbins.com

310

MATERIAL SAFETY DATA SHEET

0304029-005

318104



MSDS Ref. No: SR549M
 Date-Revised: 10/03/2003
 Revision No: 6

PRO-FAX SR549M

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: PRO-FAX SR549M
PRODUCT DESCRIPTION: Propylene/Ethylene Copolymer Pellets

MANUFACTURER

Basell Canada Inc.
 339 LaSalle Road
 Corunna, Ontario
 N0N 1G0
Product Stewardship: 410-996-1600

Basell USA Inc.
 912 Appleton Road
 Elkton, MD 21921-3920

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (U.S.): (800) 424-9300
CANUTEC: (613) 996-6666

2. COMPOSITION / INFORMATION ON INGREDIENTS

<u>Chemical Name</u>	<u>Wt.%</u>	<u>CAS#</u>	<u>EINECS#</u>
Propylene ethylene copolymer	>95	9010-79-1	
Stabilizers (trade secret)	<5		

COMMENTS: This product is not considered a hazardous material at temperatures below the melting point as determined by Basell according to the U.S. Occupational Safety and Health Act definitions and regulation, including the Hazard Communication Standard 29 CFR 1910.1200. This product is not considered a controlled substance by Basell according to Canada's WHMIS regulations. Threshold Limit Values (TLV) or Permissible Exposure Limit (PEL) values are not established. This material is not expected to cause physiologic impairment at low concentration. Until a specific TLV is adopted by ACGIH (American Conference of Governmental Hygienists), or an OSHA (Occupational Safety and Health Administration) PEL standard is issued, Basell suggests that this material be treated as a nuisance dust or particulate in accordance with the recommendations of ACGIH.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

PHYSICAL APPEARANCE: Translucent to white solid pellets

IMMEDIATE CONCERNS: Spilled material may present a slipping hazard. This product as shipped is not classified as a combustible dust; however, a combustible concentration of dust may occur if fines are suspended in air. Avoid contact with strong oxidizing agents. When working with the material at temperatures above the melting point, the material will begin to decompose producing fumes that can contain carbon dioxide, carbon monoxide, ketones, acrolein, formaldehyde, aldehydes and other unidentified organic compounds that come from the breakdown of the material. Adequate room and extruder ventilation should be provided to minimize exposures.

POTENTIAL HEALTH EFFECTS

EYES: Process vapors may irritate eyes.

SKIN: Exposure to molten resin may cause thermal burns.

INGESTION: Not Applicable

INHALATION: Process vapors may cause respiratory tract irritation.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Irritation or redness.

SKIN: Not Applicable

INGESTION: Not Applicable

INHALATION: Irritation of the nose, throat and respiratory tract.

ACUTE TOXICITY: Process vapors may cause eye and respiratory tract irritation.

CHRONIC: None Known

CARCINOGENICITY: None Known

MUTAGENICITY: None Known

REPRODUCTIVE TOXICITY

REPRODUCTIVE EFFECTS: None Known

TERATOGENIC EFFECTS: None Known

MEDICAL CONDITIONS AGGRAVATED: None Known

ROUTES OF ENTRY: Eye, Inhalation

TARGET ORGAN STATEMENT: None Known

CANCER STATEMENT: This product is not considered to be a carcinogen by OSHA, IARC or NTP.

IRRITANCY: Exposure to process vapors may cause eye and respiratory tract irritation.

SENSITIZATION: None Known

WARNING CAUTION LABELS: Burn Risk - Avoid contact with molten resin. Explosion Risk - Prevent accumulation of dust particles. Slipping Risk - Keep walking surfaces free of spilled material. Vapor Risk - Provide ventilation to avoid exposure to process vapors.

COMMENTS HEALTH: None

HEALTH HAZARDS: Process vapors may cause eye and respiratory tract irritation.

PHYSICAL HAZARDS: Spilled material may present a slipping hazard. Exposure to molten resin may cause thermal burns.

4. FIRST AID MEASURES

EYES: Flush eyes with water for 15 minutes. Get medical attention.

SKIN: Molten Resin: If molten material comes in contact with the skin, cool under ice water or a running stream of water. DO NOT attempt to remove the material from the skin. Removal could result in severe tissue damage. Get medical attention.

INGESTION: Not Applicable

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

ANTIDOTES: Not Applicable

NOTES TO PHYSICIAN: None

ADDITIONAL INFORMATION: None

5. FIRE FIGHTING MEASURES

AUTOIGNITION TEMPERATURE: Not Determined

EXTINGUISHING MEDIA: Use foam, carbon dioxide, or water spray when fighting fires involving this material.

HAZARDOUS COMBUSTION PRODUCTS: Carbon dioxide, carbon monoxide, ketones, acrolein, formaldehyde, aldehydes, unidentified organic compounds.

EXPLOSION HAZARDS: Product as shipped is not a combustible dust. However, a combustible concentration of dust may occur when fines are suspended in air.

FIRE FIGHTING PROCEDURES: Standard procedures for Class A fires.

FIRE FIGHTING EQUIPMENT: As in any fire, wear self-contained pressure demand breathing apparatus, (MSHA/NIOSH approved or equivalent) and full protective gear.

SENSITIVE TO STATIC DISCHARGE: Static discharge could be an ignition source for a combustible concentration of dust.

SENSITIVITY TO IMPACT: Not Applicable

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Sweep up material and place in a disposal container.

LARGE SPILL: Vacuum or sweep up material and place in a disposal container.

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: Keep pellets out of waterways.

LAND SPILL: Avoid runoff into storm sewers and ditches which lead to waterways.

SPECIAL PROTECTIVE EQUIPMENT: None

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Keep away from heat, sparks and flame.

HANDLING: Ground and bond containers when transferring material.

STORAGE: This product may react with strong oxidizing agents and should not be stored near such materials. Store boxes and bags of material in areas protected with automatic sprinklers.

STORAGE TEMPERATURE: 60°C (140°F) maximum

ELECTROSTATIC ACCUMULATION HAZARD: Material may accumulate static charges during transfers. Ground and bond containers when transferring material.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS: Provide adequate room ventilation. Provide adequate ventilation at the extruder to minimize exposure to process vapors. Eliminate ignition sources during repair and maintenance operations.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Wear safety glasses with side shields (or goggles).

SKIN: When handling or processing resins at elevated temperatures or in a molten state, wear protective clothing over the skin to prevent contact. Wear suitable gloves.

RESPIRATORY: A respiratory protection program that meets OSHA 1910.134, ANSI Z88.2 and/or CSA Z94.4-93 requirements must be followed whenever workplace conditions warrant use of a respirator.

OTHER USE PRECAUTIONS: Eyewash fountains and safety showers should be easily accessible.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Solid

ODOR: Slight waxy odor

APPEARANCE: Pellet
COLOR: Translucent to white
MELTING POINT: > 120°C (248°F)
SPECIFIC GRAVITY: 0.88 to 0.92

COMMENTS:

PERCENT VOLATILE: < 0.4%
WATER SOLUBILITY: Negligible

10. STABILITY AND REACTIVITY

STABLE: YES

HAZARDOUS POLYMERIZATION: NO

CONDITIONS TO AVOID: Keep away from heat, sparks and flame.

POLYMERIZATION: Product will not undergo polymerization.

HAZARDOUS DECOMPOSITION PRODUCTS: At elevated temperatures the material will begin to decompose, producing fumes that can contain carbon dioxide, carbon monoxide, ketones, acrolein, formaldehyde, aldehydes, unidentified organic compounds.

INCOMPATIBLE MATERIALS: Oxidizing materials.

11. TOXICOLOGICAL INFORMATION

GENERAL COMMENTS: None Known

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: Not Available

ECOTOXICOLOGICAL INFORMATION: Not Determined

DISTRIBUTION: Not Determined

CHEMICAL FATE INFORMATION: Not readily biodegradeable.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: (1) Recycle (reprocess). (2) Incineration including energy recovery of waste material in a permitted facility in accordance with local, state or provincial and federal regulations. (3) Landfilling in a licensed facility in accordance with local, state or provincial and federal regulations.

RCRA HAZARD CLASS: This product is not judged to be a hazardous waste by any local, state or federal regulations; however, it may be listed as industrial waste in some states or provinces. This product is not listed in the U.S. federal hazardous waste regulations, 40 CFR 261.33 paragraphs (e) or (f), i.e., chemical products that are considered hazardous if they become wastes. It does not exhibit any of the hazardous characteristics listed in 40 CFR 261 Subpart C. State or local hazardous waste regulations may apply if different from the federal.

14. TRANSPORT INFORMATION

SPECIAL SHIPPING NOTES: This product is not regulated by DOT, IMO, IATA, Canadian TDG and associated regulations, ADR or RID.

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

TITLE III NOTES: This product is not subject to SARA Title III requirements.

TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA STATUS: All ingredients in this product are in compliance with TSCA.

OSHA HAZARD COMM. RULE: This product is not considered a hazardous material at temperatures below the melting point as determined by Basell according to OSHA definitions.

CLEAN WATER ACT: This product is regulated under EPA's Clean Water Act/NPDES rules as "floating material". In addition, this product is considered "significant material" under the EPA's storm water permit rules.

CANADA

WHMIS (WORKER HAZARDOUS MATERIALS INFORMATION SYSTEM): This product is not considered a controlled substance under WHMIS. This MSDS meets WHMIS format requirements.

CANADIAN ENVIRONMENTAL PROTECTION ACT: All ingredients in this product are listed under CEPA on the DSL.

EUROPEAN COMMUNITY

EUROPEAN COMMUNITY REGULATORY: All ingredients are in compliance with EINECS/ELINCS.

16. OTHER INFORMATION

REASON FOR ISSUE: update

APPROVED BY: Richard T. LeNoir **TITLE:** Safety and Reg. Affairs Specialist

REVISION SUMMARY Revision #: 6 This MSDS replaces the August 13, 2001 MSDS. Any changes in information are as follows:
In Section 6 Land Spill Air Spill General Procedures Release Notes In Section 1 Title In Section 5 Auto Ignition (Operator) Lower ° F (Group Field)forFlashPointFlashPoint(Operator) In Section 6 Land Spill In Section 7 Special Sensitivity Loading Temperature Notes, (Group Field) for Loading Temperature Shelf Life Special Sensitivity Loading/Unloading Viscosity (Group Field) for Storage Pressure Loading Temperature Notes Storage Temperature Notes In Section 8 Skin Protection Work Hygienic Practices Clothing Protection In Section 9 Volatile Org Comp (VOC), Vapor Pressure Vapor Density Boiling Point Freezing Point Conditions (Group Field) for Density Evaporation Rate (Group Field) for Viscosity Molecular Weight Physical State

MANUFACTURER DISCLAIMER: The information contained in this Material Safety Data Sheet has been compiled from sources which Basell considers reliable and accurate to the best of Basell's knowledge. The information relates only to the specific product described above, and not to use of the product in combination with another material. Customers and other users should read this MSDS and the product label carefully before using the product. Basell neither assumes, nor authorizes anyone to assume on Basell's behalf, any liability in connection with the use of the information in this MSDS. Customers and other users should do their own testing before making commercial use of the product to ensure that the product is fit for the intended application and that the product can be used, and any waste material disposed of, safely, properly, and legally based on the customer's or other user's circumstances. BASELL MAKES NO WARRANTIES, EXPRESS OR IMPLIED, WITH RESPECT TO THE PRODUCT, INCLUDING (WITHOUT LIMITATION) WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. THE CUSTOMER OR OTHER USER OF THE PRODUCT ASSUMES ALL RISK AND LIABILITY ARISING OUT OF THE USE OF THE PRODUCT, WHETHER USED ALONE OR IN COMBINATION WITH OTHER MATERIALS. BASELL'S LIABILITY, IF ANY, FOR BREACH OF CONTRACT, BREACH OF WARRANTY, NEGLIGENCE (INCLUDING THAT OF BASELL) OR OTHER TORT, STRICT LIABILITY, OR ANY OTHER CLAIM SHALL NOT EXCEED IN AMOUNT THE PURCHASE PRICE OF BASELL PRODUCTS WITH RESPECT TO WHICH SUCH CAUSE AROSE. IN NO EVENT SHALL BASELL BE LIABLE FOR CONSEQUENTIAL, SPECIAL, OR INCIDENTAL DAMAGES.