ESD-Safe Wire Shelving

Organize workstations instantly with Wire Shelving. Easy to assemble and configure.

Strong, durable chrome finish LEWISBins+ ESD-Safe Wire Shelving features open wire design that improves visibility of stored contents, increases light and air flow and will not accumulate dirt and dust. The 800 lb. capacity shelves adjust on 1" centers along double notched posts. (600 lb. capacity for 60" x 24" and 72" x 24" shelves).

> **Starter Units** include 4 posts, 4 shelves and conductive post sleeves.

> The **Add-on Units** include 2 posts, 4 shelves, conductive post sleeves and leveling feet. Add-on units can be attached end-to-end, back-to-back, or at right angles for maximum space utilization.

> **Conductive Rubber Casters** for optimal ESD protection (200 lb. capacity ea.).

> **Conductive Post Sleeves** manufactured with a copper strip should be used in place of the plastic post sleeves to ensure shelf conductivity to ground.

> **Ground Wire** prevents the accumulation of electrostatic charges when grounding wire is in contact with a conductive floor.

> Additional **shelves** and other components are available.

W4818-63C Starter shown with DC2060-SXL

To make shelving conductive, order four (4) conductive post sleeves per shelf, a grounding wire, and/ or conductive casters.

WCP-Sleeve Conductive Post Sleeve

WCR5-S Conductive Rubber Caster

WG-Wire Ground Wire

ESD-Safe Wire Shelving

4 Shelf Starter Model	Weight (lb)	Outside Dimensions (in)			4 Shelf Add-on Model	Weight (lb)
		L	D	H		
63" Wire Shelving						
W3618-63C	52.0	36.0	18.0	63.0	WA3618-63C	45.0
W4818-63C	62.0	48.0	18.0	63.0	WA4818-63C	55.0
W6018-63C	82.0	60.0	18.0	63.0	WA6018-63C	75.0
W7218-63C	94.0	72.0	18.0	63.0	WA7218-63C	87.0
W3624-63C	66.0	36.0	24.0	63.0	WA3624-63C	59.0
W4824-63C	78.0	48.0	24.0	63.0	WA4824-63C	71.0
W6024-63C	98.0	60.0	24.0	63.0	WA6024-63C	91.0
W7224-63C	118.0	72.0	24.0	63.0	WA7224-63C	111.0
74" Wire Shelving						
W3618-74C	54.0	36.0	18.0	74.0	WA3618-74C	46.0
W4818-74C	64.0	48.0	18.0	74.0	WA4818-74C	56.0
W6018-74C	84.0	60.0	18.0	74.0	WA6018-74C	76.0
W7218-74C	96.0	72.0	18.0	74.0	WA7218-74C	88.0
W3624-74C	68.0	36.0	24.0	74.0	WA3624-74C	60.0
W4824-74C	80.0	48.0	24.0	74.0	WA4824-74C	72.0
W6024-74C	100.0	60.0	24.0	74.0	WA6024-74C	92.0
W7224-74C	120.0	72.0	24.0	74.0	WA7224-74C	112.0
84" Wire Shelving						
W3618-84C	58.0	36.0	18.0	84.0	WA3618-84C	48.0
W4818-84C	68.0	48.0	18.0	84.0	WA4818-84C	58.0
W6018-84C	88.0	60.0	18.0	84.0	WA6018-84C	78.0
W7218-84C	100.0	72.0	18.0	84.0	WA7218-84C	90.0
W3624-84C	72.0	36.0	24.0	84.0	WA3624-84C	62.0
W4824-84C	84.0	48.0	24.0	84.0	WA4824-84C	74.0
W6024-84C	104.0	60.0	24.0	84.0	WA6024-84C	94.0
W7224-84C	124.0	72.0	24.0	84.0	WA7224-84C	114.0

ESD-Safe Extra Wire Shelves

Model	Weight (lb)	Dimensions (in)	
		L	D
W3618C	9.5	36.0	18.0
W4818C	12.0	48.0	18.0
W6018C	17.0	60.0	18.0
W7218C	20.0	72.0	18.0
W3624C	13.0	36.0	24.0
W4824C	16.0	48.0	24.0
W6024C	21.0	60.0	24.0
W7224C	26.0	72.0	24.0

Note: To make shelving conductive, order four (4) conductive post sleeves per shelf, a grounding wire, and/or conductive casters.

ESD-Safe Accessories

Model	Description
WCP-Sleeve	Conductive Post Sleeves
WG-Wire	Grounding Wire
WCR5-S	5" Conductive Rubber Swivel Stem Caster
WCR5-SB	5" Conductive Rubber Swivel/Brake Stem Caster
WCR5-R	5" Conductive Rubber Rigid Stem Caster
WR18-CH	18" Rigid Channel
WR24-CH	24" Rigid Channel

Notes: Rigid casters use the corresponding rigid channel; 1 channel per pair of rigid casters. When ordering rigid casters, shelf width must be known.

All specifications are approximate and subject to change without notice.